

DECLARATION OF PERFORMANCE N. CPR-IT1/0469

- 1) Unique identification code of the product-type: **ULTRATOP LOFT W**
- 2) Intended uses: **Cementitious screed material for internal use in floor construction**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **the notified laboratory CSI S.p.A., N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A2_{fl}-s1 / A2-s1-d0
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F10
Wear resistance:	A9
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 17/02/2015



DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Reaction to fire class amended in compliance with the relevant test report
--------------------------	---

ULTRATOP LOFT W
CE MARKING
Annex to DoP N. CPR-IT1/0469



 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0469 EN 13813:2002 ULTRATOP LOFT W <i>Cementitious screed material for internal use in floor construction</i>	
Reaction to fire:	Class A2 _{fl} -s1 / A2-s1-d0
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F10
Wear resistance:	A9
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.