ADESIVI · SIGILLANTI · PRODOTTI CHIMICI PER L'EDILIZIA

Nonset 120
Declaration of Performance
N. CPR-NO1/0403

DECLARATION OF PERFORMANCE N. CPR-NO1/0403

1) Unique identification code of the product-type: **Nonset 120**

2) Intended uses: **Concrete repair product for structural and non-structural repair**

3) Manufacturer: **MAPEI AS – Vallsetvegen 6 – 2120 Sagstua (Norway) www.mapei.no**

4) Systems of AVCP: **System 2+**

System 4 for reaction to fire

5) Harmonized standards: **EN 1504-3**

Notified bodies **Sintef Building and Infrastructure, N. 1071**

6) Performances declared:

Essential characteristics	Performances
Compressive strength:	**≥ 45 MPa**
Chloride ion content:	**≤ 0,05 %**
Adhesive Bond:	**≥ 2,0 N/mm²**
Carbonation resistance:	**Pass**
Elastic modulus:	**≥ 20 GPa**
Thermal compatibility:	**≥ 2,0 MPa**
Capillary absorption:	**≤ 0,05 kg/(m²·h^{0,5})**
Dangerous substances:	**NPD**
Reaction to fire:	**Class A1**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 05/07/2022 .....

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance

DoP in Pdf format are available in the Mapei website.

Nonset 120
CE MARKING
Annex to DoP N. CPR-NO1/0403

ADESIVI · SIGILLANTI · PRODOTTI CHIMICI PER L'EDILIZIA

CE 1071	MAPEI **Valsetvegen 6 – 2021 Sagstua (Norway)** **www.mapei.no**
22 **CPR-NO1/0403** **EN 1504-3** **Nonset 120** *Concrete repair product for structural and non-structural repair*	
Compressive strength:	**≥ 45 MPa**
Chloride ion content:	**≤ 0,05 %**
Adhesive Bond:	**≥ 2,0 N/mm²**
Carbonation resistance:	**Pass**
Elastic modulus:	**≥ 20 GPa**
Thermal compatibility:	**≥ 2,0 MPa**
Capillary absorption:	**≤ 0,05 kg/(m²·h^{0,5})**
Dangerous substances:	**NPD**
Reaction to fire:	**Class A1**

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking,*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*