MEGAFIX MAXI S1
Declaration of Performance
No CPR-NO1/0472

DECLARATION OF PERFORMANCE No CPR-NO1/0472

1) Unique identification code of the product-type: **MEGAFIX MAXI S1**
2) Intended uses: **Improved cementitious adhesive for all internal and external tiling.**
3) Manufacturer: **Mapei AS - Vallsetvegen 6 - 2120 Sagstua - Norge (Norway) - www.mapei.no**
4) Harmonized standards: **EN 12004:2007+A1:2012**

No: Notified bodies:

0370 LGAI TECHNOLOGICAL CENTER, S. A.(Applus+)

0767 Kiwa MPA Dresden GmbH

5) Performances declared and Assessment and Verification of Constancy of Performance (AVCP):

Essential characteristics	Performances	AVCP
Reaction to fire:	**Class $A2_{FL}$-s1/ A2-s1,d0**	**3**
Bond strength:	**expressed as:** **- initial tensile adhesion strength ≥ 1,0 N/mm²**	**3**
Durability of bond strength against: **- climate/heat ageing action:** **- water/humidity action:** **- freeze-thaw cycles:**	**expressed as:** **- tensile adhesion strength after heat ageing ≥ 1,0 N/mm²** **- tensile adhesion strength after water immersion ≥ 1,0 N/mm²** **- tensile adhesion strength after freeze-thaw cycles ≥ 1,0 N/mm²**	**3**
Release of dangerous substances:	**NPD**	**-**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

MEGAFIX MAXI S1
Declaration of Performance
No CPR-NO1/0472

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 29/09/2026

.....

The DoP in PDF format are available on our website.

Revision 10 notes:	*General update after the adoption of new software.*

MEGAFIX MAXI S1
***Annex to DoP No* CPR-NO1/0472**
Additional information

REACH information: *the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that the manufacturer makes available on the website along with this current Declaration of Performance.*

CE 0370, 0767	MAPEI **Vallsetvegen 6 - 2120 Sagstua - Norge (Norway)** **www.mapei.no**
22 **CPR-NO1/0472** **EN 12004** **MEGAFIX MAXI S1** Improved cementitious adhesive for all internal and external tiling.	
Reaction to fire:	Class $A2_{FL}$-s1/ A2-s1,d0
Bond strength:	expressed as: - initial tensile adhesion strength ≥ 1,0 N/mm^2
Durability of bond strength against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles:	expressed as: - tensile adhesion strength after heat ageing ≥ 1,0 N/mm^2 - tensile adhesion strength after water immersion ≥ 1,0 N/mm^2 - tensile adhesion strength after freeze-thaw cycles ≥ 1,0 N/mm^2

The manufacturer supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*