DECLARATION OF PERFORMANCE No CPR-NO1/0491

1) Unique identification code of the product-type: **UNIPLAN 500**
2) Intended uses: **Cementitious screed material for internal use in floor construction.**
3) Manufacturer: **Mapei AS - Vallsetvegen 6 - 2120 Sagstua - Norge (Norway) - www.mapei.no**
4) Harmonized standards: **EN 13813:2002**

No:	Notified bodies:
----	**----**

5) Performances declared and Assessment and Verification of Constancy of Performance (AVCP):

Essential characteristics	Performances	AVCP
Reaction to fire:	**Class $A1_{FL}$**	**4**
Release of corrosive substances:	**CT**	**4**
Water permeability:	**NPD**	**-**
Water vapour permeability:	**NPD**	**-**
Compressive strength:	**C20**	**4**
Flexural strength:	**F5**	**4**
Wear resistance:	**NPD**	**-**
Sound insulation:	**NPD**	**-**
Sound absorption:	**NPD**	**-**
Thermal resistance:	**NPD**	**-**
Chemical resistance:	**NPD**	**-**

UNIPLAN 500
Declaration of Performance
No CPR-NO1/0491

6) Appropriate Technical Documentation: **No "UNIPLAN 500". Reaction to fire class declared without the need for testing according to the Commission Decision 2010/85/EU. Organic material < 100% by weight. Maximum layer thickness 4 mm.**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 05/11/2026

.....

The DoP in PDF format are available on our website.

Revision 10 notes:	*General update after the adoption of new software.*

UNIPLAN 500
***Annex to DoP No* CPR-NO1/0491**
Additional information

REACH information: *the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that the manufacturer makes available on the website along with this current Declaration of Performance.*

CE ----	**Vallsetvegen 6 - 2120 Sagstua - Norge (Norway)** **www.mapei.no**
24 **CPR-NO1/0491** **EN 13813** **UNIPLAN 500** Cementitious screed material for internal use in floor construction.	
Reaction to fire:	Class $A1_{FL}$
Release of corrosive substances:	CT
Compressive strength:	C20
Flexural strength:	F5

The manufacturer supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*