ADESIVI · SIGILLANTI · PRODOTTI CHIMICI PER L'EDILIZIA

Uniplan 550 Zero
Declaration of Performance
N. CPR-NO1/0492

DECLARATION OF PERFORMANCE N. CPR-NO1/0492

1) Unique identification code of the product-type: **Uniplan 550 Zero**
2) Intended uses: **Cementitious screed material for internal use**
3) Manufacturer: **MAPEI AS – Vallsetvegen 6 – 2120 Sagstua – Norway - www.mapei.no**
4) Systems of AVCP: **System 4**
5) Harmonized standards: **EN 13813:2002**

   Notified bodies: **No tasks for the notified body**

6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	**Class $A1_{FL}$**
Release of corrosive substances:	**CT**
Water permeability:	**NPD**
Water vapour permeability:	**NPD**
Compressive strength:	**C30**
Flexural strength:	**F5**
Wear resistance:	**NPD**
Sound insulation:	**NPD**
Sound absorption:	**NPD**
Thermal resistance:	**NPD**
Chemical resistance:	**NPD**

7) Appropriate Technical Documentation: **Included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 2010/85/EU.**

   Organic material < 100 % by weight **Maximum layer thickness 4 mm**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 21/08/2024 .....

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	*First issue*

Uniplan 550 Zero
CE MARKING
Annex to DoP N. CPR-NO1/0492

CE	**MAPEI** **Vallsetvegen 6 – 2120 Sagstua (Norway)** **www.mapei.no**
24 **CPR-NO1/0492** **EN 13813** **Uniplan 550 Zero** *Cementitious screed material for internal use*	
Reaction to fire:	**Class A1FL**
Release of corrosive substances:	**CT**
Water permeability:	**NPD**
Water vapour permeability:	**NPD**
Compressive strength:	**C30**
Flexural strength:	**F5**
Wear resistance:	**NPD**
Sound insulation:	**NPD**
Sound absorption:	**NPD**
Thermal resistance:	**NPD**
Chemical resistance:	**NPD**

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking,*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*